



## Shieldex<sup>®</sup> Med-tex P130 + B

1150902130B



<b>Raw Material</b>	78 % Polyamide + 22 % Elastomer
<b>Type of knit</b>	Stretch-Tricot
<b>Metal Plated</b>	Silver
<b>Material Composition</b>	(63 % PA /18 % EL / 19 % Ag) ± 10 %
<b>+ B Coating</b>	Nitrile rubber as additional protective coating
<b>Stretch</b>	Double stretch direction / elongation warp 55- 205 % / weft 85-125 %
<b>Abrasion Resistance</b>	≤ 9000 cycles
<b>Total Weight</b>	130 g/m <sup>2</sup> ± 18 %
<b>Total Thickness</b>	0.55 mm ± 15 %
<b>Roll Width</b>	132 ± 5 cm
<b>Roll Length</b>	Max. 36 m
<b>Temperature Range</b>	-30 °C to 80 °C
<b>Storage and Handling</b>	According to our care and handling instructions
<b>Compliance and Certification</b>	OEKO-TEX <sup>®</sup> STANDARD 100, DIN EN ISO 9001:2015, REACH, RoHS, Screening test using a praxis-near carrier test system following ISO 18184:2019 against the Bovine Coronavirus

**Alterations Reserved 01.01.2022/19** – The above information has been compiled from our manufacturer area according to the latest state of development and application technology. Since application and further processing are beyond our control, no liability of the producer can be derived from the contents of the data sheet. All deviant or transcending data sheet information must be confirmed in written form by the manufacturer. Our general terms and conditions apply in all cases. All previous data sheets are invalid with the publication of this data sheet. Please note our handling and storage instructions as well accessible at [www.shieldex.de](http://www.shieldex.de).

**Physical Address**  
V Technical Textiles, Inc  
320 South Main Street  
Newark, NY 14513

**Mailing Address**  
V Technical Textiles, Inc  
4502 State Rt. 31  
Palmyra, NY 14522

**Contact**  
Phone: (315)-597-1674  
Fax: (315)-597-6687  
[info@vtechttextiles.com](mailto:info@vtechttextiles.com)

